

INSTALLATION GUIDE



Attachmate®

DATABridge™



DATABridge 6.2

Host, Enterprise Server, and Client



© 2013 Attachmate Corporation. All rights reserved.

No part of the documentation materials accompanying this Attachmate software product may be reproduced, transmitted, transcribed, or translated into any language, in any form by any means, without the written permission of Attachmate Corporation. The content of this document is protected under copyright law even if it is not distributed with software that includes an end user license agreement. The content of this document is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Attachmate Corporation. Attachmate Corporation assumes no responsibility or liability for any errors or inaccuracies that may appear in the informational content contained in this document.

Attachmate and the Attachmate logo are registered trademarks and DATABridge is a trademark of Attachmate Corporation in the USA.

All other trademarks, trade names, or company names referenced herein are used for identification only and are the property of their respective owners.

A copy of the Attachmate software license agreement governing this product can be found in a 'license' file in the root directory of the software distribution.

Third party notices (if any) can be found in a 'thirdpartynotices' file in the root directory of the software distribution.

Attachmate Corporation
1500 Dexter Avenue North
Seattle, WA 98109 USA
+1.206.217.7100
<http://www.attachmate.com>

Contents

DATABridge Installation Guide	5
New Features in 6.2	6
Security Guidelines	8
System Requirements	9
Description of Files on the Installation Image	12
Related Documentation	14
Installing DATABridge on Windows	15
Installer Advanced Tab	17
Run the Migrate Program on Windows	18
The Working Directory	19
Updatepath Dialog Box	21
Client Configuration Dialog Box	21
Installing the DATABridge Client on UNIX	23
Install the DATABridge Client on UNIX	23
Run the Migrate Program on UNIX	26
Install the Client Console on UNIX	28
Installing the DATABridge Host	29
Before You Upgrade the DATABridge Host	29
Back Up Changes to Host Files	30
Install the DATABridge Host	34
Set Up Guardfiles	35
Setting Up a Relational Database	37
Setting Up a SQL Server Database (Windows)	37
Create an ODBC Data Source	38
Setting Up an Oracle Database (Windows)	40
Setting Up a User ID	40
Signon Configuration	41
Signon Parameters	41
Integrated Windows Authentication for Microsoft SQL Server	42
Using an Existing Database	42
Getting Started	45
Next Steps for the DATABridge Client	45
Start Enterprise Server	49

Installation Results	51
OBJECT/DATABRIDGE Directory	51
Files Installed with DATABridge Host	53
SYMBOL/DATABRIDGE Directory	53
WFL/DATABRIDGE Directory	55
DATA Directory	56
PATCH Directory	57
Files Installed with DATABridge Enterprise Server	59
Files Installed with the DATABridge Client and Client Console	60

CHAPTER 1

DATABridge Installation Guide

In this Chapter

New Features in 6.2	6
Security Guidelines	8
System Requirements	9
Description of Files on the Installation Image	12
Related Documentation	14

This guide is useful for system administrators who are tasked with installing, configuring, and running DATABridge. It contains instructions for installing and upgrading the Attachmate DATABridge Host, Enterprise Server, and Client products. Also included are a list of new features, system requirements, and installation results for these products.

To install DATABridge FileExtract, Plus, Twin, or DMSII Client, see the documentation for that product, located in the Docs folder on the installation image. These documents are in PDF format and require Adobe Reader to view them.

To install, configure, and run this program, you should be a system administrator familiar with the following:

- Standard Unisys® operations for MCP-hosted mainframes such as the CS7xxx series, Libra series, ClearPath® NX/LX or ASeries
- DMSII databases and Data And Structure Definition Language (DASDL)

New Features in 6.2

DATABridge 6.2 contains the following features and enhancements.

Installation

Combined installer for Windows

You can install DATABridge components more easily on Windows with the Attachmate Installer Program. This installer standardizes the installation process and makes it easier to deploy the DATABridge Client and Enterprise Server. When your software is installed, the installer starts up a utility to help you configure security and other settings.

64-bit versions of Enterprise Server and the Client Console for Windows

You can now run native versions of DATABridge Enterprise Server and the DATABridge Client Console on 64-bit Windows operating systems.

The Attachmate Installer Program provides a 64-bit JRE (version 1.0.6_26), available from the **Feature Selection** tab of the Attachmate Installer Wizard.

Security

File security for Enterprise Server and DATABridge Client

Access to configuration files and directories can now be restricted to administrators and approved users and groups.

File security for DATABridge Enterprise configuration and log files is automatically enabled during installation. By default, any user in the Administrators group has read-write access to the configuration files. (Log files are always read-only.)

File security for the Client's global working directory can be enabled after your software is successfully installed (see step 6 of *Installing DATABridge on Windows* (page [15](#))).

For details, see *Security Guidelines* (page [8](#)).

Keys masked from screen output

In a continued effort to enhance security, keys no longer appear in on-screen messages. Because keys can contain sensitive data, they now appear only in log files to which Administrators have access.

DATABridge Client

Ability to interact with Client service using command files

The Batch Console automates routine Client tasks by allowing command files/shell scripts launched by the Client service to interact with the service. For more information, see the *DATABridge Client Administrator's Guide*.

<i>Blackout option to enforce "down time" between client runs</i>	You can schedule blackout periods during which the Client suspends all processing and updates to allow for routine maintenance or reporting. To use this feature with the service-controlled Client, set the Blackout Period value from the Client Console (Data Source > Client Configuration > Processing > Scheduling).
<i>Alternate method of updating</i>	Systems that use relational database replication in order to update a copy of the relational database can employ a new form of update processing that selectively updates only those columns whose values have changed. This form of update processing, referred to as <i>optimized column updates</i> , significantly increases the efficiency of replication between relational databases (for example, from Oracle to Oracle). You can enable this feature (globally or for individual data sets) from the Client Console by selecting Optimize Column Updates in the Client Configuration dialog box, or by modifying the client configuration parameter <code>optimize_col_updates</code> .
<i>New columns from DMSII reorganizations match those in DMSII database</i>	Enhancements to the Reorganization command scripts (created by the <code>redefine</code> command) allow the Client to retrieve the initial value for a new column added by a DMSII reorganization.

DATABridge Enterprise Server

<i>Bidirectional file transfer</i>	Enterprise Server can now copy files both to and from the MCP environment. For details, see "Bidirectional File Transfer" in the DATABridge Enterprise Server Help.
------------------------------------	---

All-Product

<i>Support for DMSII level 55.1 (MCP 14.1)</i>	DATABridge 6.2 is compatible with DMSII level 55.1 (MCP 14.1), which allows for large ALPHA items and data obfuscation.
<i>Support for data sets that contain DMSII LINKS</i>	DATABridge now supports DIRECT, UNORDERED, and STANDARD data sets that contain DMSII links. Links in variable-format data sets are cloned, but not tracked. For more information, see Chapter 5, "DMSII and Relational Database Data Mapping" in the <i>DATABridge Client Administrator's Guide</i> .
<i>IPv6 support</i>	DATABridge now supports IPv6 addresses in addition to IPv4 addresses.

Security Guidelines

To protect your data, make sure that you implement the security guidelines recommended by Unisys and the manufacturer for your relational database.

For	To decrease security risk
DATABridge Host	<p>Install DATABridge Host to the Unisys mainframe under its own privileged usercode. This is preferable to installing under the usercode of the DMSII database. If you install and run DATABridge under multiple usercodes, you must install a copy of DBEngine under each of those usercodes. Alternatively, you can establish DBEngine as a system library (SL). However, this is not recommended as it may expose your data to greater security risk by allowing unauthorized access to the DBEngine.</p>
DATABridge Client	<p>File security helps to protect Client operations by restricting access to the working directory and the command-line client to the owner/administrator and any users they approve. In Windows, enable the option Enable File Security at installation (or run the program <code>setfilesecurity.exe</code> after installation) and set user privileges via Windows user groups. Groups with administrator privileges will have read-write access to the client files.</p> <p>In UNIX, you restrict file access via your entries in the file <code>globalprofile.ini</code>. See <i>Install the DATABridge Client on UNIX</i> (page 23).</p>
DATABridge Enterprise Server	<p>File security is automatically enabled when you install DATABridge Enterprise. File security protects the configuration and log files by restricting privileges on the PC to users who need to modify the configuration.</p> <p>By default, any user in the Administrators group can modify the configuration files and delete the read-only log files. If you create a user group in Windows called DBEAdmins, only the users in that group will be able to alter the configuration files and delete log files. Likewise, if you create a group called DBEUsers, only the users in that group will be able to view the configuration. For more information, see "Implementing Security for DBEUsers and DBEAdmins Groups" in the DATABridge Enterprise Server Help.</p>

System Requirements

To install and run DATABridge 6.2, your system must meet the following hardware and software requirements. Specific requirements vary based on your hardware and other software components present.

DATABridge Host	<p>Unisys mainframe system with an MCP level SSR 49.1 through 55.1</p> <p>DMSII software (including the DMALGOL compiler)</p> <p>DMSII database DESCRIPTION, CONTROL, DMSUPPORT library, and audit files</p> <p>Access to an audited DMSII database</p>
DATABridge Enterprise Server	<p>Note: This list assumes that the Enterprise Server machine is connected to a Unisys mainframe system running DATABridge Host 6.x and to a system running DATABridge Client 6.x.</p> <p>ClearPath PC with Logical disks or MCP disks (VSS disks in MCP format)</p> <p>-or-</p> <p>Windows PC that meets the minimum requirements of its operating system, which is one of the following:</p> <ul style="list-style-type: none"> ▪ Windows 7 ▪ Vista ▪ Windows 2008 R2 (64-bit only) ▪ Windows Server 2008 ▪ Windows Server 2003 <p>Visibility to MCP disks on a storage area network (recommended)</p> <p>TCP/IP transport</p> <p>An Internet browser is required to view the application Help. JavaScript must be enabled to use navigation, search, and other Help features. Supported browsers include Internet Explorer (IE), Firefox, and Google Chrome.</p>
DATABridge Client Console	<p>You can install Client Console to the same machine as the Client; however, this can drain resources and impact the performance of your relational database. Instead, we recommend that you install the Client Console to a machine that connects to the Client machine via TCP/IP transport.</p> <p>Java Runtime Environment (JRE) version 6 Update 26 (1.60_26) or later. To reduce security threats and vulnerabilities, we recommend that you download the JRE from www.java.com and configure it to receive updates automatically.</p>

DATABridge Client

Note: Disk space requirements for replicated DMSII data are not included here. Your relational database should have, at minimum, twice as much disk space as the DMSII data you plan to clone. For best results, use a RAID disk array and store the client files on a separate disk from the database storage.

Client - Windows

Unisys ES7000

-or-

Pentium PC processor 1 GHz or higher (multiple CPU configuration recommended)

2 GB of RAM (4 GB recommended)

100 GB of disk space (in addition to disk space for the relational database built from DMSII data)

TCP/IP transport

One of the following operating systems:

- Windows Server 2008 R2
- Windows Server 2008
- Windows Server 2003
- Windows 7
- Windows Vista
- Windows XP Professional

One of the following databases:

- Microsoft SQL Server 2012
- Microsoft SQL Server 2008 R2 (up to SP1)
- Microsoft SQL Server 2005 (up to SP4)
- Oracle 9i, 10g, 11g

**Client - UNIX
and Linux**

One of the following systems:

- Sun Microsystems SPARCstation running Solaris 10 or later, and Oracle 9i, 10g Release 2, or 11g
- Hewlett Packard Itanium with HP-UX 11i v3 (B11.31) running Oracle 10g Release 2, or 11g
- Hewlett Packard 9000 Series 700 or 800 with HP-UX 11i v2 running Oracle 10g Release 2, 11g, or 9i
- IBM pSeries running AIX 5L or newer, and Oracle v9i or 10g Release 2 or 11g
- Intel Pentium with Red Hat Enterprise Linux Release 4 or later, SUSE Linux Enterprise Server 11 SP1 or later, or UBUNTU Linux 7.1 or later running Oracle 9i, 10g Release 2 or 11g

2 GB of RAM (4 GB recommended)

100 GB of free disk space for installation (in addition to disk space for the relational database built from DMSII data)

TCP/IP transport

Note: On HP-UX Itanium, Oracle 11g supports only 64-bit applications. For Oracle 9i on Linux, we provide only a 32-bit client.

Description of Files on the Installation Image

This topic lists the directories and files on the installation image, in alphabetical order. DATABridge Host installation files (CDINSTALL, DISKINSTALL, IMAGE, and INSTALL) are located on the root. Both 32-bit and 64-bit versions are provided for all DATABridge Clients, except DB2 (32-bit only).

This directory	Contains	File description
AIX	Tar files for installing DATABridge clients on the AIX platform:	
	DB_AIX64_Ora9i.tar	The 64-bit client for Oracle 9i
	DB_AIX64_Ora10g2.tar	The 64-bit client for Oracle 10g (release 2)
	DB_AIX64_Ora11g.tar	The 64-bit client for Oracle 11g
	DB_AIX_Ora9i.tar	The 32-bit client for Oracle 9i
	DB_AIX_Ora10g2.tar	The 32-bit client for Oracle 10g (release 2)
Console	Files for installing the DATABridge Client Console, in the following subdirectories:	
	HP-UX (Itanium)	dbconfig-hpux.motif.ia64_32.tar.gz
		dbconsole-hpux.motif.ia64_32.tar.gz
	Linux	dbconfig-linux.gtk.x86.tar.gz
		dbconfig-linux.gtk.x86_64.tar.gz
		dbconsole-linux.gtk.x86.tar.gz
dbconsole-linux.gtk.x86_64.tar.gz		
SunOS	dbconfig-solaris.gtk.sparc.tar.gz	
	dbconsole-solaris.gtk.sparc.tar.gz	
Docs	DATABridge Help documentation files in PDF format. Help for Enterprise Server and the Client Console are available from the Help menu of the application.	
HP-UX	Tar files for installing clients on Hewlett Packard ® 9000 series machines running HP-UX 11i v2 or later:	

	DB_HP-UX_Informix.tar	The 32-bit client for Informix.
	DB_HP-UX_Ora9i.tar	The 32-bit client for Oracle 9i
	DB_HP-UX_Ora10g2.tar	The 32-bit client for Oracle 10g (release 2)
	DB_HP-UX_Ora11g.tar	The 32-bit client for Oracle 11g
	DB_HP-UX64_Informix.tar	The 64-bit client for Informix.
	DB_HP-UX64_Ora9i.tar	The 64-bit client for Oracle 9i
	DB_HP-UX64_Ora10g2.tar	The 64-bit client for Oracle 10g (release 2)
	DB_HP-UX_Ora11g.tar	The 32-bit client for Oracle 11g
HP-UX (Itanium)	Tar files for installing clients on Hewlett Packard ® Itanium machines running HP-UX 11i v2 or later:	
	DB_HP-UXi_Ora10g2.tar	The 32-bit client for Oracle 10g (release 2)
	DB_HP-UXi64_Ora10g2.tar	The 64-bit client for Oracle 10g (release 2)
	DB_HP-UXi64_Ora11g	The 64-bit client for Oracle 11g
Linux	Tar files for installing clients on Intel® X86 series machines running various flavors of Linux including RedHat Enterprise (Release 4 or 5), SUSE or UBUNTU:	
	DB_Linux_Ora9i.tar	The 32-bit client for Oracle 9i
	DB_Linux_Ora10g2.tar	The 32-bit client for Oracle 10g (release 2)
	DB_Linux_Ora11g.tar	The 32-bit client for Oracle 11g
	DB_Linux64_Ora10g2.tar	The 64-bit client for Oracle 10g (release 2)
	DB_Linux64_Ora11g.tar	The 64-bit client for Oracle 11g

SunOS	Tar files for installing clients on Oracle SPARCstation running Solaris 10:	
	DB_SunOS_Ora9i.tar	The 32-bit client for Oracle 9i
	DB_SunOS_Ora10g2.tar	The 32-bit client for Oracle 10g (release 2)
	DB_SunOS_Ora11g.tar	The 32-bit client for Oracle 11g
	DB_SunOS64_Ora9i.tar	The 64-bit client for Oracle 9i
	DB_SunOS64_Ora10g2.tar	The 64-bit client for Oracle 10g (release 2)
	DB_SunOS64_Ora11g.tar	The 64-bit client for Oracle 11g
Windows32	Installation files for 32-bit versions of Enterprise Server, the DATABridge Client (Windows), and the Client Console.	
Windows64	Installation files for 64-bit versions of Enterprise Server, the DATABridge Client (Windows), and the Client Console.	

Related Documentation

When using DATABridge, you may need to consult the following resources.

DATABridge product documentation

In the DOCS folder on the DATABridge installation image, you'll find guides for installation, error codes, and a separate administrator's guide for each DATABridge product. These documents require Adobe Reader for viewing, which you can download from the Adobe website at <http://get.adobe.com/reader/>. All DATABridge product documentation, including technical notes, is also available on the Attachmate website at <http://support.attachmate.com/manuals/databridge.html>.

Documentation for DATABridge Enterprise Server and the DATABridge Client Console is also available from the **Help** menu. A modern browser is required for viewing.

Unisys MCP server documentation

If you are not completely familiar with DMSII configuration, refer to your Unisys documentation.

CHAPTER 2

Installing DATABridge on Windows

Use this procedure to install or upgrade the following DATABridge products:

- DATABridge Client
- DATABridge Client Console
- DATABridge Enterprise Server

Before you install

The installer gives you the option to secure the DATABridge Client working directory. The **Enable File Security** option appears after the DATABridge Client is successfully installed (step 5 of this procedure). When this option is selected, you can assign access rights to user IDs and groups. File security for DATABridge Enterprise Server is automatically enabled during installation. For more information, see *Security Guidelines* (page 8).

Important: The working directory location has changed in this release for both the DATABridge Client and DATABridge Enterprise Server. If you're upgrading, browse to your current working directory to ensure that your data sources are upgraded.

To install DATABridge

- 1 Log on using a Windows account with administrator privileges.
- 2 To start the installer, do one of the following:
 - From the Windows64 or Windows32 folder, double-click Setup.exe.
 - From the download site, click the Windows download link, select a location for the installer files, and then click **Next**.
- 3 In the Installer wizard, accept the license agreement and click **Continue**.
- 4 In the tabbed window, make your selections and then click **Install Now**:

File Location Specify a location for the DATABridge program files (or accept the default).
tab This path is saved as the INSTALLDIR string value for the Windows registry key.

Feature Selection Click the DATABridge component you want to install and choose **Feature will be installed on local hard drive**. (Items with a red "x" won't be installed.)
tab Follow the same procedure to optionally install Japanese Support and Localization.

Options tab Configure settings for DATABridge components that are selected on the **Features Selection** tab.

For the Client, specify the working directory location and the TCP/IP port on which the service listens for connection requests. If you're upgrading, click **Browse** and select the existing working directory.

Important: Do not specify the Program Files directory as the Client working directory.

For Enterprise Server, specify a path for the configuration files and a TCP/IP port value in the range of 1024 - 65535. If you're upgrading, click **Browse** and select the existing working directory. Use the default port numbers unless they're already in use by another program.

Advanced tab Specify the type of installation you want and your log file options.

- 5 (Client Installation) To restrict read/write access to program files and directories, in the **Client Configuration** (page [21](#)) dialog box, select **Enable File Security** and then enter the user ID and groups that will have access to Client files and directories. You can also enable Client File Security after installation by running setfilesecurity.exe.
- 6 (Client Installation) If you plan to run the client from the command line, specify whether to add the client directory to the user path (recommended) or the system path. For a description of these options, see **Updatepath dialog box** (page [21](#)).
- 7 If you're upgrading, *run the Migrate program* (page [18](#)) to complete the installation.

After installation is complete, see the Getting Started section of this guide.

Related Topics

Installer Advanced Tab

[17](#)

Installer Advanced Tab

- 1 Run the Attachmate Setup wizard (`setup.exe`).
- 2 Click the **Advanced** tab.

Install to this PC

Installs the selected DATABridge components to your computer.

Create an Administrative Install image on a server

Note: An administrative installation does not actually install the product. Instead, it creates an installation image that you can use to deploy DATABridge users.

When you create an administrative installation image, an image of DATABridge is copied to a network location for later installation to multiple workstations. This network location can be used by deployment tools to access and create packages that are deployed to workstations. Also, end users can perform installations by running `setup.exe` from this location.

Log file settings

By default an installation log file is created, but this file is deleted if the installation succeeds. (This configuration avoids accumulation of large log files after successful installations.) To save a log file for all installations, including successful ones, select **Create a log file for this installation**, and clear **Delete log file if install succeeds**.

The installation log file, which provides details about the installation, is saved in the user's temp directory (`%tmp%`) with a generated name that begins with `atm`. To open this folder, launch the Start menu Run command and enter `%tmp%`.

Run the Migrate Program on Windows

Use this procedure to upgrade Client files from 6.1 and earlier, after installing DATABridge Client 6.2. To install the Client, see *Installing DATABridge on Windows* (page [15](#)).

To run the Migrate program

- 1 If you are upgrading from the DBLIB SQL Server client, make sure that you have an ODBC data source in the Windows Control Panel. Make sure to create a SYSTEM (not a USER) data source name.
- 2 Open a command prompt and type migrate. (If you didn't add the DATABridge program directory to the system PATH during installation, type the full filename, including path, for migrate and enclose it in quotation marks.

The Migrate program creates a new global working directory for the Client and then a new working directory for each migrated data source. After updating the configuration file parameters and creating the service configuration file, the Migrate program moves user scripts and configuration files from the previous version to these directories. If you selected **Enable File Security** during installation, the DATABridge Client's global working directory and all files and folders will be re-created and secured.

- 3 Respond to the prompts:
 - If you answer "yes" and provide the working directory, the Migrate program will find your data sources and migrate them. Skip the remaining steps.
 - If you answer "no" or do not provide the path to the working directory. Complete the remaining steps.
- 4 Enter the name of each data source and its working directory, using the path with drive letter or a directory and name relative to the current directory.
- 5 Repeat step 4 for each data source. When you're done, enter an empty line (that is, <CR>).

The Migrate program creates a working directory for each data source. The existing configuration file is used to create a new binary configuration file in the `config` subdirectory. Deprecated parameters are removed or replaced by the equivalent parameters. User scripts are moved to the `scripts` subdirectory. The Migrate program then starts the `dbfixup` program, which upgrades the client control tables and populates the `dbscripts` directory for each data source.

If the `read_null_records` parameter is set to True, the Migrate program copies the Null Record files for the data sources to the `config` subdirectories. A new Client service configuration file is created (`dbcontrol.cfg`), which includes updated data sources and any existing scheduling parameters. The Migrate program runs a `dbutility generate` command for each data sources to populate the `dbscripts` directories.

Note: If you need to re-run the Migrate program for any reason, first delete the global working directory created by the Migrate program.


The Working Directory

The DATABridge Client's global working directory (also referred to as the *service's working directory*) is required for the Client to run. The *working directory* is different from the *install directory*, where the installer copies all of its files.

- On UNIX, you must create a new working directory each time you install or upgrade the software.
- On Windows, the working directory is created for you in the location you specify in the Installer wizard. If you're upgrading or if you enabled file security, a new working directory is created. This path is saved as the `INSTALLDIR` string value in the Windows registry key.

Contents of the Client Working Directory

The working directory contains four subdirectories: `config`, `locks`, `logs`, and `scripts`.



This subdirectory	Contains
<code>config</code>	<p>The program-generated file (<code>log.cfg</code>) that keeps track of the current log file and the binary configuration file (<code>dbcontrol.cfg</code>), which the service updates when you make changes to settings in the Client Console.</p> <p>If you export the service configuration file, the exported copy (<code>dbcontrol.ini</code>) is created in this subdirectory. When you add a data source, a backup copy of the service configuration file <code>dbcontrol.cfg</code> is created (<code>dbcontrol.bak</code>).</p>
<code>locks</code>	<p>Lock files for each data source. A lock file is created the first time a client run starts. The file is re-opened on subsequent runs and kept open for the duration of the run to prevent additional runs using the same data source. This replaces the functionality of the <code>client_activity</code> column in the <code>DATASOURCES</code> client table. The <code>-u</code> option can no longer be used in command-line runs.</p> <p>The locks subdirectory is created the first time you start the service (new installations) or when you run the Migrate program (upgrades).</p>
<code>logs</code>	<p>Log files (<code>*.log</code>) created by the service. A section in the configuration file named <code>[Log_File]</code> allows the user to set the criteria for switching log files. For more information, see Appendix C in the <i>DATABridge Client Administrator's Guide</i>.</p>

`scripts` Command files that are launched by the service when a client run terminates with a non-zero exit status.

Each Data Source Has a Working Directory

Each data source requires its own separate working directory within the Client working directory. This directory is created automatically when you add a new data source in the Client Console or when you upgrade existing data sources using the Migrate program. If you use the command-line client (`dbutility`), you must create directories for your data sources. When `dbutility` executes a `configure` or a `define` command, it creates the subdirectories (if they don't exist) and a binary configuration file (`dbridge.cfg`) in the `config` subdirectory.

The data source working directory contains the following subdirectories:

This subdirectory	Contains
<code>config</code>	<p>The client configuration file (<code>dbridge.cfg</code>). For runs initiated by the Client service, this file must be binary. The command-line client can use a binary or a text file. For details, see Appendix C in the <i>DATABridge Client Administrator's Guide</i>. Make sure that you delete any exported text configuration files (<code>dbridge.ini</code>) that are no longer used. These become obsolete when the configuration is updated from the Client Console.</p> <p>The Null record file for the data source and two program-generated files (<code>log.cfg</code> and <code>trace.cfg</code>), which keep track of the current log and trace files.</p> <hr/> <p>Note: You can make the Client add signon information to the configuration files it creates by running the <code>configure</code> or a <code>define</code> commands with switches to specify your signon parameters. For more information, see <i>Signon Configuration</i>. (page 41)</p>
<code>dbscripts</code>	Files created by the generate command, SQL scripts, bulk loader files (<code>*.ctl</code> , <code>*.fmt</code>), and command files and shell scripts to invoke the bulk loader. In Oracle, the control files also specify parameters for SQL*Loader. The DB2 client creates DB2 command files, which contain DB2 commands to perform the load. These files are named <code>db2load.tablename</code> .
<code>discards</code>	Files created by the client or the bulk loader when they encounter a data record that cannot be processed. If the Client determines that a DMSII record is bad before handing it to the bulk loader, it puts this record in the client discard file as if it was an insert operation. The data is encoded as an SQL stored procedure call using the appropriate stored procedure based on the type of update.
	<p>Discard files can be executed using the database's query tool:</p> <ul style="list-style-type: none"> ▪ SQL Server Management Studio query window ▪ Oracle SQL*Plus utility ▪ DB2 command-line processor
<code>logs</code>	Client log files. The filename includes a user-configurable prefix followed by a date (<code>yyyymmdd</code>). If multiple log files exist for the same date, a time (<code>_hhmmss</code>) is appended to the end of the filename.

`scripts` User script files.

The data source working directory also contains temporary files. Many of these files aren't removed by the Client and should be deleted periodically. You can safely delete them any time the Client is not running (except during the interval between a `redefine` command and a `reorg` command). Temporary files include: trace files; bcp log files; an unload file; scripts that are executed by the `redefine` command; and temporary files used by the Windows client during data extraction.

Updatepath Dialog Box

Getting there

- 1 Run the Attachmate Setup wizard (`setup.exe`).
- 2 On the **Feature Selection** tab, select the DATABridge Client, and click **Install Now**.
- 3 After you make selections in the **Client Configuration Options** dialog box, the **Updatepath** dialog box opens.

If you run the Client from a command line, use the **Updatepath** dialog box to include the Client directory in the system path. The **Updatepath** dialog box won't appear when reinstalling or repairing the installation.

This setting	Does this
Do not add DATABridge program directory to the PATH	Requires that you manually add the DATABridge directory each time you run a DATABridge program from the command line. Choose this setting if you use scripts that specify the full path for the client.
Add DATABridge program directory to System PATH	Makes the DATABridge programs (and directory) available to anyone who uses the computer by adding the DATABridge directory to the Windows Path environment variable. Avoid this option if security is a concern.
Add DATABridge program directory to the User PATH	Makes the DATABridge programs available only to the user who installed the program. Choose this setting only if you run multiple versions of the client, different types of clients, or use scripts that specify the full path to run the client and do not add the DATABridge program directory to the PATH.

Client Configuration Dialog Box

Working directory for the DATABridge Client Service Displays the working directory you selected in the Options tab of the installer. You can change it by entering a different path or by clicking **Browse**. This directory is required for all client operations, whether initiated from a command line or by the service.

File Security

Enable File Security Select this check box to set the security attributes for the Client working directory, its files and folders, according to the settings specified in this dialog box..

UserID and Optional Groups When **Enable File Security** is selected, you can specify a user or group that has read-write privileges to all directories and files created by the Client program (in addition to administrators and the built-in system account, which have these privileges by default). You can specify both individual users and groups if the user is not a member of the group. Optionally, you can specify a group that has read-only privileges to these files.

UserID for dbutility Specify the user ID that has full read-write control of the DATABridge Client and its programs. dbutility commands can must be run under this user ID or by a member of the group specified in the DBAdministrator Group string in the Windows registry.

Note: If you reinstall DATABridge, this value will be populated with the current ID, which you can clear and reenter, if needed.

DBAdministrator Group Specify a group name whose members can run DATABridge Client and its programs and have read-write access to files in the Client working directory.

DBOperator Group (Optional) Specify a group name whose members can monitor client operations by reading the DATABridge Client log, but cannot run the Client or change the configuration settings.

Installing the DATABridge Client on UNIX

This section provides instructions for installing and upgrading the DATABridge Client software, including the Client Console and daemon, on a UNIX system.

Install the DATABridge Client on UNIX

Use this procedure for first-time installations and upgrades on all UNIX, Linux, and related systems. In this procedure, you'll install the Client, create a Client working directory, and specify a user ID for the daemon.

Important: Commands, filenames, and often, passwords, are case-sensitive on UNIX systems. Type the commands as shown.

To install the Client on UNIX

- 1 Log on using a userid that has root privileges.
- 2 If a previous version of the DATABridge Client is running on your system, stop it.
- 3 Create a new install directory for DATABridge 6.2 (for example, "/opt/dbridge62").
- 4 Move the appropriate tar files (Client, Client Console) to the UNIX system using binary FTP. See *Description of Files on the Installation Image* (page [12](#)).

- 5 Change the directory to the install directory you created in step 3 and extract the tar file:

```
tar -xvf filename
```

where *filename* is the full tar filename, including location.

The extract program creates a client subdirectory named after the database (for example, Oracle). Files are extracted to this subdirectory and to the directory you specified.

- 6 Next, change the owner and group for the files in the install directory to the userid (and the group to which the userid belongs) designated to run the DATABridge Client (that is, the USERID specified in the file *globalprofile.ini*). To do this, type the following command:

```
chown -R dbridge:users *
```

where *dbridge* is the user ID and *users* is the corresponding group.

CAUTION: To prevent the files in the install directory from being accidentally deleted, we recommend that you leave them set to read-only (the default). Before you update the software, to prevent the extraction from failing, either remove all of the files from the install directory or make them writeable until the update is successfully installed.

- 7 In the editor, open the sample daemon script file (*dbdaemon*) located on the root of the install directory, update the necessary environment variables, and then save *dbdaemon* to the following location:
 - On Linux and Solaris: */etc/init.d*
 - On HP-UX: *sbin/init.d*

- 8 Create the directory `/etc/Attachmate/DATABridge/6.2`
- 9 In the editor, open the `globalprofile.smp` file on the root of the install directory and make the following changes:

Caution: This file is critical for client operations. If this file is missing or contains the wrong information, the client will not run.

- a) For `INSTALLDIR`, specify the install directory you created in step 3.
 - b) For `WORKINGDIR`, specify the full name of the Client's working directory for 6.2. If you're upgrading, make sure that the working directory for 6.2 is different from your 6.0 or 6.1 working directory. You create the actual directory later in this procedure.
 - c) For `USERID`, specify the user under which you'll run the daemon. When you start the daemon, you must log in as this user or as the root user. Clients can only be run under this userid.
 - d) To enable file security for the Client working directory, specify a value for `umask`. The bits specified get removed from the default file security bits. A `umask` of `027` (the default) indicates that the owner bits are unchanged, but the group's `w` and `x` bits are reset and all 3 bits are reset for other users. For a stronger mask, specify a value such as `077`.
- 10 Save the file as `globalprofile.ini` to the directory `/etc/Attachmate/DATABridge/6.2`.
 - 11 Do one of the following:
 - (New installations) In the home directory, use the editor to update your profile (for example, `.profile` or `.bash_profile`) and include the environment variable `ORACLE_HOME`. Consult the Oracle database administrator to determine what this variable should be set to (typically, it's `/opt/oracle...`). You must also include the directory `$ORACLE_HOME/bin` in the `PATH` to ensure that the bulk loader `sqlldr` can be located. You may want to also include the environment variable `INSTALLDIR`, which points to the directory created in step 3. You can then add the Client program directory `$INSTALLDIR/Oracle` to the `PATH`, making it a lot easier to run the Client from the command line.
 - (Upgrades - Optional) Update your profile so that the `PATH` points to the newly-installed Client.
 - 12 For the DATABridge Client to find the Oracle shared libraries, add the Oracle lib (or lib32) directory to the appropriate environment variable for your system, as shown in the following table. The line you add after the `ORACLE_HOME` definition can be used instead of typing the complete Oracle lib directory name.

To update	Add the following to your profile
All 64-bit clients	<code>LD_LIBRARY_PATH = \$LD_LIBRARY_PATH:\$ORACLE_HOME/lib</code>
32-bit clients on Solaris or Linux	<code>LD_LIBRARY_PATH = \$LD_LIBRARY_PATH:\$ORACLE_HOME/lib32</code>
32-bit clients on AIX	<code>LIBPATH = LIBPATH:\$ORACLE_HOME/lib32</code>

32-bit clients `SHLIB_PATH = SHLIB_PATH:$ORACLE_HOME/lib32`
 on HP-UX

Note: The UNIX shell you use may require that you add a line that exports the environment variable. For instructions, consult your UNIX documentation.

- 13 Using the value you specified in step 9b, create a Client working directory for 6.2 that contains the three subdirectories `config`, `locks` and `logs`. (For upgrades, the Migrate program creates a new, secure working directory and subdirectories from this value. See *Run the Migrate Program on UNIX* (page [26](#)).
- 14 When installation is complete, verify that the Client directory files are correctly installed. For a list of installed files, see *Files Installed with the DATABridge Client and Client Console* (page [58](#)).
- 15 If you run the Client from a command line, you must also update the environment variable `PATH` in your profile to include the directory that contains the DATABridge Client. If you installed the Client to the directory `/opt/dbridge62`, add `:/opt/dbridge62/Oracle` to the `PATH`. The `PATH` is defined as:

```
PATH=$PATH: ... $ORACLE_HOME/bin: ...
```

where each specified directory is terminated by a colon, except for the last one on the line.

Individual clients use the database names as the directories names (for example, Oracle).

Important: Make sure that the `mknod` utility's directory (usually `/usr/sbin`) is included in the `PATH`. If the shell scripts used to clone data sets cannot find this utility, files will be used in place of named pipes resulting in bulk loader problems, such as broken pipes.

- 16 Do one of the following:
 - If you're upgrading, proceed to *Run the Migrate Program on UNIX* (page [26](#)) to complete the installation.
 - If you're installing for the first time, install the Client Console to configure the Client parameters. See *Install the Client Console on UNIX* (page [28](#)).

Run the Migrate Program on UNIX

Use this procedure to upgrade DATABridge Client 6.1 and earlier on UNIX systems.

To run the Migrate program

- 1 Install the DATABridge Client 6.2. See *Install the DATABridge Client on UNIX* (page [23](#)).
- 2 Make sure that the file `globalprofile.ini` includes values for `INSTALLDIR`, `USERID`, and `WORKINGDIR`. (For instructions, see *Install the DATABridge Client UNIX* (page [23](#))). The client runs under the specified `USERID` in the `globalprofile.ini`.
- 3 Log on using a `userid` that has root privileges.
- 4 Open a command session and type `migrate`. If the Client directory wasn't added to the `PATH` during installation, you must type the full path to `migrate`.

The Migrate program first creates a new global working directory and then creates a working directory for each migrated data source. Next, it moves the existing user scripts and configuration files to this directory after updating the configuration file parameters. It also creates the daemon configuration file which contains any scheduling information defined for the individual data sources.

- 5 The program asks if you are upgrading from version 6.x and actively use the daemon. If the answer is yes, enter the full filename of the 6.x global working directory. Make sure that you enter a different name for the 6.2 working directory. Data sources from the earlier version will be migrated to the new working directory structure. Skip the remaining steps.
- 6 When prompted, enter the name of each data source. Next, enter the location of the working directory for this data source (either as a full filename including the drive letter or a name relative to the current directory, starting with a directory name).

The Migrate program creates a working directory for each data source. Existing settings are used to create a new binary configuration file in the `config` subdirectory and user scripts are moved to the `scripts` subdirectory. The Migrate program starts the `dbfixup` program, which upgrades the client control tables and populates the `dbscripts` directory for each data source. Lastly, the Migrate program applies file security to the working directory, data source directories, and all Client files.

If the `read_null_records` parameter is set to `True`, the Migrate program copies the Null Record files for the data sources to the `config` subdirectories. A new daemon configuration file is created (`dbcontrol.cfg`), which includes updated data sources and any existing scheduling parameters. The Migrate program runs a `dbutility generate` command for each data sources to populate the `dbscripts` directories.

- 7 To run the Client using the daemon, install the Client Console—preferably to a different machine than the relational database to avoid using valuable system resources.

You can run the command-line program (`dbutility`) or the daemon after you create a script for the daemon that includes the updated `ORACLE_HOME`, `INSTALLDIR`, and `WORKING_DIR` parameters.

Note: If you need to re-run the Migrate program at any point, first delete the working directory that was created by the Migrate program.

Install the Client Console on UNIX

For optimal performance, install the Client Console to a workstation *connected to—not on*—the relational database, or it will use valuable system resources. You can install and run the Client Console on AIX, Linux, Solaris, and Windows operating systems. For example, you can install and run it on a Windows workstation that is connected to UNIX, or run it on both types of workstations simultaneously. See *System Requirements* (page [9](#)).

Note: Use DATABridge Client Console 6.2 with DATABridge 6.2 software. It is not compatible with earlier DATABridge versions.

To install the Client Console

- 1 Copy the *.tar.gz archives from the \Console\<UNIX> directory for the appropriate UNIX platform to the location you want.

There are two archives; one for the dbconfig and one for dbconsole.

- 2 Unzip the archives:

```
gzip -d dbcon*.gz
```

- 3 Extract each of the files from the tarballs by running the following separate commands:

```
tar -xvf dbconsole*.tar
tar -xvf dbconfig*.tar
```

This creates two directories (dbconsole and dbconfig) in the current working directory.

- 4 Next, provide execute privileges to the dbconfig file and to the dbconsole file:

```
chmod +x dbconsole/dbconsole
chmod +x dbconfig/dbconfig
```

- 5 Open the dbconfig.ini and dbconsole.ini files and edit the paths of the configuration and workspace to reflect the current install directory (where you extracted the files in step 3).

After the Client Console is successfully installed, *start the daemon* (page [44](#)) and then *start the Client Console* (page [46](#)).

CHAPTER 3

Installing the DATABridge Host

In this Chapter

Before You Upgrade the DATABridge Host	29
Install the DATABridge Host	34
Set Up Guardfiles	35

This chapter includes instructions for installing and upgrading the DATABridge Host software on the MCP server.

Before You Upgrade the DATABridge Host

Before you upgrade, please note the following:

- Some files are overwritten by the installation. If you have modified these files, use the following section to write down your changes before you run DATABridge Installation WFL. After installation, you can edit the new files with your changes. We also recommend that you make backup copies of these files using the `copy` command. For example:

```
copy DATA/= as SAVE/DATA/=
copy SYMBOL/= as SAVE/SYMBOL/=
copy WFL/= as SAVE/WFL/=
```
- You must recompile any tailored support libraries after you upgrade. See the *DATABridge Host Administrator's Guide*.
- You can use Accessory parameter files from DATABridge 5.2 with DATABridge 6.1 or later. If DATABridge 6.x includes new options you want to use, you can add them by typing them into your existing parameter file.

Back Up Changes to Host Files

Use this section to write down changes you've made to host files before you run DATABridge Installation WFL. After you install, update the new files accordingly.

DATABridge Support Library

If you changed SYMBOL/DATABRIDGE/SUPPORT, note the changes you made and make the corresponding changes to the new SYMBOL/DATABRIDGE/SUPPORT.

DATABridge Compile WFL

If you changed WFL/DATABRIDGE/COMP, note the changes you made and make the corresponding changes to the new WFL/DATABRIDGE/COMP.

Option	Your Setting
--------	--------------

QUEUE =

STARTTIME =

BDNAME =

Other:

Other DATABridge WFL Files

In any DATABridge WFL file, you can modify STARTTIME, QUEUE, and the number of printer backup files. If you changed any of the following DATABridge WFL files, write your changes in the tables that follow. After installation, update the files accordingly.

WFL/DATABRIDGE/SPAN

Option	Your Setting
--------	--------------

QUEUE =

STARTTIME =

BDNAME =

WFL/DATABRIDGE/LISTER

Option	Your Setting
--------	--------------

QUEUE =

STARTTIME =

BDNAME =

WFL/DATABRIDGE/SERVER

Option	Your Setting
QUEUE =	
STARTTIME =	
BDNAME =	
USERCODE =	

WFL/DATABRIDGE/TANKER

Option	Your Setting
QUEUE =	
STARTTIME =	
BDNAME =	

WFL/DATABRIDGE/SNAPSHOT

Option	Your Setting
QUEUE =	
STARTTIME =	
BDNAME =	

WFL/DATABRIDGE/COPYAUDIT

Option	Your Setting
QUEUE =	
STARTTIME =	
BDNAME =	
KEEP =	

Other

WFL/DATABRIDGE/AUDITTIMER

Option	Your Setting
QUEUE =	
STARTTIME = (initial start)	
BDFNAME =	
STARTTIME = (queued start)	

WFL/DATABRIDGE/DBINFO

Options	Your Setting
QUEUE =	
STARTTIME =	
BDFNAME =	

DBEngine CONTROL File

The DATA/ENGINE/CONTROL file is overwritten with the new DATABridge key. If you made changes to any of the following options, make a note of them now.

Option	Your Setting
Checkpoint client every n audit blocks	
Audit Level =	
Property Level =	
Workers=	
Available From...To...=	
ReadAhead =	
Links =	

SAMPLE Files

If you did not rename SAMPLE DATABridge CONTROL files before you changed them, save them with a different name now. The SAMPLE files are as follows:

DATA/AUDITTIMER/SAMPLE/CONTROL

DATA/AUDITMIRROR/SAMPLE/CONTROL

DATA/GENFORMAT/SAMPLE/CONTROL

DATA/LISTER/SAMPLE/CONTROL

DATA/SERVER/SAMPLE/CONTROL

DATA/ENGINE/SAMPLE/CONTROL

To use any of the new options, type them in your parameter file. SAMPLE files should only be used as templates to construct files.

Install the DATABridge Host

Before you install, you'll need to determine the usercode and pack that you'll use to install. For best results, we recommend that you choose a privileged usercode and the primary pack. Use the following procedure to install the DATABridge host software.

To install the DATABridge Host

- 1 **Sign in to the privileged usercode.** If you install from DVD to a nonprivileged usercode, all object files will be marked as restricted, which causes the installation WFL to pause (as explained in step 4).

- 2 **Copy the DATABridge installation WFL (WFL/DATABRIDGE/INSTALL) to the host.**

- If you're installing from uploaded files, upload DISKINSTALL and IMAGE files using a file transfer tool capable of binary/image transfers to the privileged usercode where DATABridge is to be installed. Sign on to the usercode, and then use the following command:

```
WFL UNWRAP *= AS = OUTOF IMAGE
```

- If you're installing from the DVD, decompress the file

```
WFL UNWRAP *= AS = OUTOF *CDINSTALL FROM DB62 (KIND=CDROM)
```

In the WFL file, change DATABRIDGE to the version-specific DVD name and save the file:

```
G WFL/DATABRIDGE/INSTALL
```

```
REP /FROM DATABRIDGE/ /FROM DB62/ : T
```

```
SA
```

- 3 **If you're upgrading, back up the DATA/ENGINE/CONTROL directory in case problems exist with new keys.**

- 4 **Start the DATABridge Installation WFL.**

```
START WFL/DATABRIDGE/INSTALL
```

When prompted, respond with "OK<Transmit>", and then enter DATABridge keys.

- 5 **For first-time installations, create a new DBServer control file:**

```
COPY DATA/SERVER/SAMPLE/CONTROL AS DATA/SERVER/CONTROL
```

- 6 **Edit the DBServer control file:**

- a) Change SOURCE *<datasourcename>* to the name of the data source that the client uses.

- b) (Optional) Change TCP/IP Port = 11367 (the default) to the port you use.
 - c) Change Database = DESCRIPTION/<dbname> ON <packname> to reflect the usercode/location of the description file for the database to be cloned.
- 7 **(Recommended) Enable the DATABridge Plus software for near real-time access to audit files.** Execute the following command (replacing <usercode> and <pack> with your values):

```
SL DBAUDITSUPPORT=( <usercode> )OBJECT/DATABRIDGE/AUDITSUPPORT ON
<pack>:TRUSTED, LINKCLASS=3
```

8 Start the DATABridge Server.

If you are upgrading, you must first bring down the server using the AX QUIT command.

```
START WFL/DATABRIDGE/SERVER
```

After you've successfully installed the DATABridge Host software, do the following:

- Recompile your tailored support libraries. Enter the following command (replacing <usercode>, <dbname>, and <pack> with your values):


```
START WFL/DATABRIDGE/COMP ("SUPPORT", "( <usercode> )<dbname> on
<pack>")
```

For more information, see the *DATABridge Host Administrator's Guide*.
- If your database uses guardfiles, you can include DATABridge under database guardfile validation. See *Set Up Guardfiles* (page [35](#)).
- For information about security options, see "DATABridge Security" in the *DATABridge Host Administrator's Guide*.

Set Up Guardfiles

If your database uses guardfiles, DATABridge can be included under database guardfile validation. For validation of guardfiles to work, the relevant guardfile must specify read access (RO) for the DATABridge Accessory and/or the usercode under which the DATABridge Accessory is running.

In addition, the DATABridge (DBEngine) must have read access to the actual database guardfile. You can accomplish this in one of the following ways:

- Run the DATABridge Accessory under the usercode that owns the guardfile. For example, if the guardfile is (PROD)GUARDIAN/FILE, run the Accessory under the PROD usercode.
- Change the security of the guardfile to PUBLIC IN.
- Make sure that DBEngine is a privileged program. DBEngine is marked as a privileged program on the release tape.

Note: Access to the guardfile itself is enforced by the MCP. Therefore, even if you make the database visible to the Accessories, you must still give DBEngine read access to the guardfile, as explained above.

DATABridge Components and Guardfiles

DATABridge Accessories and the DATABridge Server Workers (but not the DATABridge Server itself) must have read access to the database (physical or logical) they are using. No other rights are necessary. Since GenFormat and DBInfo (when searching for a quiet point) always use the physical, rather than a logical, database, they must have read access to the physical database only.

DBEngine and Extract Workers

The DBEngine and its Extract Workers must have OPENUPDATE access to the physical database. This allows the extract routines to set markers in the audit trail and to switch the active audit file. In addition, the Extract Workers require FIND access for reading the data set records during a clone.

Here's an example of guardfile fragments for a physical database. (In this example, the fictional site runs up to three Extract Workers and has DATABridge software installed under the (DB) usercode on the family named DBPACK.)

```
PROGRAM (DB)OBJECT/DATABRIDGE/DBINFO ON DBPACK = RO;
PROGRAM (DB)OBJECT/DATABRIDGE/GENFORMAT ON DBPACK = RO;
PROGRAM (DB)OBJECT/DATABRIDGE/ENGINE ON DBPACK = RW,
DMVERBS = (OPENINQUIRY, OPENUPDATE);
PROGRAM (DB)EXTRACT/WORKER/0 = RW,
DMVERBS = (OPENINQUIRY, OPENUPDATE, FIND);
PROGRAM (DB)EXTRACT/WORKER/1 = RW,
DMVERBS = (OPENINQUIRY, OPENUPDATE, FIND);
```

The DMVERBS list for the physical database prevents any actual updating because DELETE, STORE, etc., are not allowed.

If you allow more than two Extract Workers to run concurrently, add entries like the ones above with the appropriate number for the last node.

Accessories and DATABridge Server Workers

The Accessories and DATABridge Server Workers (but not the DATABridge Server itself) must be listed in the guardfile that protects the database they will be using. However, if they use a logical database instead of a physical database, put these entries in the guardfile that protects the logical database.

Here's an example of guardfile fragments for a physical or logical database. (In this example, DATABridge is installed under the (DB) usercode on the family named DBPACK and the DATABridge Clients run on hosts called IPADDRESS1 and IPADDRESS2.)

```
PROGRAM (DB)OBJECT/DATABRIDGE/SPAN ON DBPACK = RO;
PROGRAM (DB)OBJECT/DATABRIDGE/SNAPSHOT ON DBPACK = RO,
PROGRAM (DB)OBJECT/DATABRIDGE/LISTER ON DBPACK = RO;
PROGRAM (DB)OBJECT/DATABRIDGE/TANKER ON DBPACK = RO;
PROGRAM (DB)OBJECT/DATABRIDGE/AUDITTIMER ON DBPACK = RO;
PROGRAM (DB)DBSERVER/WORKER/1 ON IPADDRESS1 = RO;
PROGRAM (DB)DBSERVER/WORKER/1 ON IPADDRESS2 = RO;
PROGRAM (DB)DBSERVER/WORKER/2 ON IPADDRESS1 = RO;
PROGRAM (DB)DBSERVER/WORKER/2 ON IPADDRESS2 = RO;
```

If you allow more than two DATABridge Server Workers to run concurrently, add entries like the ones above with the appropriate number for the last node.

CHAPTER 4

Setting Up a Relational Database

In this Chapter

Setting Up a SQL Server Database (Windows)	37
Setting Up an Oracle Database (Windows)	40
Setting Up a User ID	40
Signon Configuration	41
Using an Existing Database	42
Getting Started	45

This chapter covers instructions for setting up a relational database to receive DMSII data.

Setting Up a SQL Server Database (Windows)

The SQL Server Client uses only the data source parameter to connect to ODBC. The database and server parameters (required to run BCP) are retrieved from the ODBC data source.

In addition, the following applies to Microsoft SQL Server:

- The default schema for the DATABridge user determines the ownership of tables
- DATABridge Client 6.x uses only the ODBC client. The ODBC client places no restrictions on the user's schema when using SQL Server 2005 or later.
- You can use primary keys with non-clustered indexes without having to edit the scripts generated by the client.
- The SQL Server Client supports the data type bigint (which can be used for numeric data) and the SQL Server 2008 data types date, datetime2 and time. To maintain backward compatibility for bigint, enable the parameter use_bigint.

To use the DATABridge Client with Microsoft SQL Server

Note: On Microsoft SQL Server 2012, if you plan to use Integrated Windows Authorization with the DATABridge Client (thereby running the service from the default account), you must add NT AUTHORITY\SYSTEM to the sysadmin Server Role. In the Microsoft SQL Server 2012 Management Studio, use the left pane to navigate to **Security > Server Roles**, right-click **sysadmin**, select **Properties**, and click the **Add** button.

1. Create an ODBC data source, unless one already exists. (See *Create an ODBC Data Source* (page [38](#)).)
2. Make sure you have enough space free for the Microsoft SQL Server database.

3. If your DMSII data sets contain case-sensitive ALPHA key items, using the default Microsoft SQL Server installation may result in duplicate keys. To avoid this, perform a custom installation of Microsoft SQL Server and set the Sort Order to Dictionary, case-sensitive. The only way you can change sort order case-sensitivity is via installation.

Create an ODBC Data Source

Use this procedure to set up an ODBC data source. If you have not created a new SQL Server database, and are not using an existing database, you must create a new database as outlined in the previous section. This database will hold your DATABridge Client control tables and the replicated DMSII tables.

To create an ODBC Data Source

- 1 Click **Start > Settings > Control Panel > Administrative Tools**. Within **Administrative tools**, double-click **Data Sources (ODBC)**.
 - 2 In the **ODBC Data Source Administrator**, click the **User DSN** or System **DSN** tab. System DSN data sources are available to all users on this computer, recommended if you use a service. User DSNs are limited to the user who created them.
 - 3 Click the **Add** button.
 - 4 In the **Create New Data Source** dialog box, choose one of the following from the list of drivers and click **Finish**:

SQL Native Client	Choose this option if you use multi-threaded updates.
SQL Server	
 - 5 In the **Create a New Data Source to SQL Server** wizard, name the data source, such as its database name followed by DS. You will enter this name as the data source parameter value in the DATABridge configuration file.
 - 6 In the **Server** field, choose your local computer name, and then click **Next**.
 - 7 To connect to this data source, choose an authentication method, and then click **Next**:

Integrated Windows authentication	SQL Server uses the credentials of the currently logged in user to validate the login. Most installations use Integrated Windows authentication.
SQL Server authentication	DATABridge connects to SQL Server using the user ID/password pair specified in the DATABridge configuration file.
 - 8 Specify the database you created in the first step as the default ODBC database.
- Note: You should never use the master database or any of the other system databases as the default.
- 9 Click **Finish** to create the ODBC data source.

If you installed the DATABridge Client software for the first time, you must configure the user ID as well as the password, server, and database. See *Set Up a SQL Server Database (Windows)* (page [37](#)).

Setting Up an Oracle Database (Windows)

The following notes apply to Oracle:

- The Oracle clients have a configuration parameter that allows you to specify a rollback segment, specifically one that is much larger than the default rollback segment. Rollback segments are used to construct a SET TRANSACTION USE ROLLBACK SEGMENT SQL statement that is executed at the start of every transaction.
- The Oracle clients support the CLOB data type for holding DMSII ALPHA items that are too large for the VARCHAR2 data type. The parameters in PL/SQL stored procedures for these clients limit the CLOB data type to 32K (Oracle 11g) and 16K (Oracle 10g2 and 9i). For backward compatibility, this feature is enabled via the `use_clob` parameter.
- The Windows clients work with all recent Oracle databases including Oracle 9i, 10g, and 11g.
- Starting in Oracle 11g Release 2, Oracle database passwords are case-sensitive.
- The OCI_SUCCESS_WITH_INFO status displays the reason for any error that occurs.

The Oracle `open_cursors` Parameter

It is recommended that you add the `open_cursors` parameter to the `initSID.ora` file. Depending on the setting of the `aux_stmts` parameter, you may need to increase the value of `open_cursors` to make it slightly higher than the value of `aux_stmts`.

If `open_cursors` is not set high enough, an error occurs, indicating that the maximum number specified was exceeded. Refer to your Oracle documentation for information on setting these values.

Setting Up a User ID

If you're installing DATABridge Client software for the first time, you must set up a user ID that allows the client to access the relational database.

Microsoft SQL Server

If you are the Microsoft SQL Server database administrator (DBA) or if you have a user ID with DBA privileges, set up a user ID for the DATABridge Client that has the following.

Caution: Do not use the `sa` user ID to run the DATABridge Client. The `sa` user ID typically owns tables that the DATABridge Client should not have access to.

- (Required) The ability to select from any table, including system tables. DATABridge reads the data dictionary to determine if a table or procedure exists.
- (Required) The ability to create tables, stored procedures, and indexes for tables that the user ID owns.
- (Optional) Unlimited space usage. This is recommended because of the large amounts of data that can be replicated from a DMSII database.

To include rights to modify the database as needed, use the DATABridge owner (db_owner) to set up the user ID. After you set up the user ID, you must configure the user ID, password, server, and database. For instructions, see *Signon Configuration*. (page [41](#))

Oracle

If you are the database administrator (DBA), or if you have a user ID with DBA privileges, set up a user ID for the DATABridge Client that has the following. Note that Oracle version 11g R2 and later uses case-sensitive passwords.

Caution: Do not use IDs such as SYS, SYSTEM, or SYSMAN to run the DATABridge Client. These user IDs typically own tables that the DATABridge Client should not have access to.

- (Required) The ability to select from any table, including system tables. It is highly recommended that you configure the user ID with DBA privileges.
- (Required) The ability to create tables, stored procedures, and indexes for tables that the user ID owns.
- (Optional) Unlimited tablespace privileges. This is recommended because of the large amounts of data that can be replicated from a DMSII database.

For information on creating a user ID, see your Oracle documentation.

Signon Configuration

If you have installed the DATABridge Client software for the first time, you must supply the appropriate logon parameters to your relational database. In addition, you may be required to supply a password to sign on to the DATABridge Server on the host.

You do this from the Client Console when you create a new data source, using the Host and Port boxes in the **Add Data Source** dialog box. If a KEY is specified for the source in the DATA/SERVER/CONTROL, enter this for in the **Password** box. These settings are saved to the binary Client configuration file (dbridge.cfg), which automatically encodes passwords.

If you supply logon parameters via dbutility command-line options, you must type them each time you run dbutility.

Note: Configuration file settings override environment variables. However, command-line options override both configuration file settings and environment variables. If you are upgrading from an earlier DATABridge Client, the program honors the environment variables DBSERVER, and DBHOSTPW in addition to those listed in the Signon Parameters.

Signon Parameters

The following table shows signon parameters in the dbutility configuration file (dbridge.cfg) and their equivalent command-line options.

Configuration file parameter	Command-line option	Description
user	-U	Specifies the user ID for the relational database. The user ID must have read and write access to the designated

		database.
password	-P	Specifies the password associated with the user ID for the relational database. Note that Oracle 11g and later uses case-sensitive passwords. Configuration file only: If the password contains non-alphanumeric characters besides the underscore (<code>_</code>), you must enclose it in double quotation marks, as follows: <code>password = "a\$bb%"</code>
database	-D	For Oracle, this name identifies the Oracle instance or Net8 service being accessed. If the service name contains non-alphanumeric characters, they must be enclosed in double quotation marks, as follows: <code>database = "orcl.databridge.com"</code>
datasource	-O	For the DATABridge SQL Server client, this parameter is the name that identifies the ODBC data source, as configured within the Windows Control Panel. For the DB2 client, this parameter is the CLI data source name, which is actually the database name.
use_nt_authen	-W	When the ODBC data source uses Integrated Windows authentication, set this parameter to True (or yes). When the ODBC data source uses SQL Server Authentication (using userid and password), set it to False (or no). If you set this parameter incorrectly, the client will work, but bcp loader operations will fail.

Integrated Windows Authentication for Microsoft SQL Server

The Microsoft SQL Server database provides two methods for database user authentication. SQL Server authentication uses a userid/password mechanism to authenticate user connections to SQL Server. Integrated Windows authentication relies on the Windows operating system to authenticate user connections to SQL Server.

Note: The DATABridge Client requires a user account with administrator privileges when using Integrated Windows authentication to access SQL Server. For details about `use_nt_authen`, see [signon] in Appendix C of the *DATABridge Client Administrator's Guide*.

Using an Existing Database

You can use an existing relational database for receiving DMSII data. However, DATABridge Client will create its own tables to hold the DMSII data instead of using any existing tables.

DATABridge Client creates two sets of tables:

- **Control tables.** These tables hold the layout information of the DMSII database and relational databases. They also state information that the client needs for communicating with DBEngine or Enterprise Server.

- **Data tables.** These tables hold the data replicated from the DMSII database

Caution: If you place any constraints on the tables that the DATABridge Client creates, the DATABridge Client will not work correctly.

Before You Use an Existing Database

If you plan to use an existing relational database, first complete the following:

- Back up the database in accordance with the documentation that came with your relational database.
- (UNIX) Make sure that the database is installed on a raw device and your client software is installed on a different system. This is recommended for optimum performance.
- Create a new user ID for running the DATABridge Client. The DATABridge Client only accesses tables it owns.

Important! Verify that no tables exist with the same names, especially with the names of DATABridge Client system tables. If existing tables have the same name as DMSII data sets or DATABridge Client system tables, rename those tables first. Otherwise, the tables will be overwritten.

CHAPTER 5

Getting Started

In this Chapter

Next Steps for the DATABridge Client	45
Start Enterprise Server	49

Next Steps for the DATABridge Client

After the installation is complete, you can start using the DATABridge Client. If you're using the DATABridge Client for the first time, we recommend that you run it from the Client Console.

If you're upgrading and want to start using the Client Configurator to customize your relational database, see *Switch from User Scripts to the Client Configurator* (page [48](#)).

If you're upgrading and plan to run the Client from a command line, use your existing Client configuration file. See Appendix C in the *DATABridge Client Administrator's Guide* for information about configuration parameters.

Start the Service

If you installed the Client Console, use one of the following procedures to start the service (Windows) or daemon (UNIX).

To start the service (Windows)

- 1 From the **Start** menu, choose **Settings > Control Panel > Administrative Tools > Services**.
- 2 In the **Services** window, double-click **Attachmate DATABridge 6.2 Client Service**, and then click the **Start** button.

If the service doesn't start, the specified port may be in use. Check the service log file in Documents and Settings\All Users\Application Data\Attachmate\DATABridge\6.2\logs.
- 3 To stop the service, select **Attachmate DATABridge Client 6.2 Service**, and click **Stop**.
- 4 (Optional) On the recover tab, specify that the service is restarted after the first or second failures. (Do not set more than two failures; if the service fails more than that, you'll want a service failure to inform you of the problem.)
- 5 Start the Client Console and follow the instructions to add the service.

To start the daemon (UNIX)

- 1 Log in using the user ID you specified for the daemon in step 7 of *the installation instructions* (page [23](#)) or as a user with root privileges. If you start the daemon from the root (for example, by typing `su`), the daemon automatically assumes the specified user ID.
- 2 Specify the appropriate environment variables. If you use Oracle, add the Oracle bin directory to the PATH and the Oracle lib directory to the library path environment variables. Failure to do this will cause the bulk loader scripts to not find `sqlldr`.
- 3 Start the daemon by typing the following:

```
/etc/init.d/dbdaemon start
```

The daemon automatically creates the `config` and `logs` subdirectories for the data source working directory, and then places a binary configuration file (`dbcontrol.cfg`) in the `config` subdirectory. This configuration file is updated each time you add a new data source in the Client Console.

Note: You can start or stop the service anytime by manually running the script with the appropriate options (start or stop).

- 4 If you're using the Client Console, see *Start the Client Console* (page [47](#)).

Introducing the Batch Console

The Batch Console automates routine Client tasks by allowing command files/shell scripts launched by the Client service to interact with the service. It interprets a source file that contains a set of statements written in a language similar to Visual Basic. These statements can initiate a connection, perform rudimentary tests, and issue console requests, to the service. For example, by using the Batch Console in an end-of-run script, you can run a program that restarts the Client after daily reports are generated.

To use the Batch Console, you must first create a source file for the Batch Console and place it in the `scripts` directory of the service's working directory (also referred to as the Client's global working directory). We recommend that you use a file extension that allows you to easily identify this file as a Batch Console source file (for example, `.bcs`). You can debug this source file by running the Batch Console from the command line, using the source filename (including directory, such as `scripts\source_filename`) as the first argument of the Batch Console command.

The Batch Console always runs as a background run. Its activity is written to a log that uses the source filename with the extension `.log` added to it. For example, if your source filename is `sourcefile.bcs` the log file is named `sourcefile.bcs.log`.

Start the Client Console

After the service has been started, start the Client Console and connect to the service. See *Starting the Service* (page [46](#)).

To start the Client Console on Windows

- 1 From the **Start** menu, choose **Programs > Attachmate DATABridge > DATABridge Client Console 6.2**.
- 2 From the Client Console, click the **Help** menu, and then click **Help Contents** or **Cheat Sheets** for instructions on getting started.

To start the Client Console on UNIX

- 1 From a command line, run the following command

```
cd <install_path>/dbconsole
```

where `<install_path>` is the location to which you installed the Client Console.

- 2 Next, run the following command:

```
./dbconsole &
```

- 3 From the Client Console, click the **Help** menu, and then click **Help Contents** or **Cheat Sheets** for instructions on getting started.

Switch from User Scripts to the Client Configurator

If you currently customize your database via user scripts but wish to start using the Client Configurator, you must first run the `dbscriptfixup` program for each of your data sources. This program updates the client control tables so that you no longer need the user scripts. The `dbscriptfixup` program also creates a new set of user scripts that are compatible with the Client Configurator for backup purposes.

Note: This task is not time-sensitive and can be completed at any time after installation. We recommend that you get the DATABridge Client 6.2 running to your satisfaction before you perform this task.

To run `dbscriptfixup`

- 1 Create a backup copy of your user scripts.
- 2 Open a command prompt and change the directory to the working directory of a data source.
- 3 Run the `dbscriptfixup verify` command (replacing `<data_source>` with the actual name):

```
dbscriptfixup verify <data_source>
```

The `dbscriptfixup` program performs a read-only review of the user scripts and reports changes you must make to the scripts.

- 4 Make any changes if indicated by the `dbscriptfixup` program and then repeat step 2 until you get no errors. You may want to remove or rename problem user scripts and deal with them later.
- 5 Back up the control tables for the data source to an unload file by typing the following command:

```
dbutility unload <data_source> <data_source>_control_tables.sav
```

- 6 Run the `dbscriptfixup upgrade` command:

```
dbscriptfixup upgrade <data_source>
```

- 7 Depending on the results of step 6, do one of the following:
 - If the command succeeded (exit code=0), you can now use the Client Configurator. If you want to verify the process, see the following section.
 - If the command failed (exit code=1), reload your control tables by typing the following command and then replace any user scripts you changed in step 4 to restore the configuration to its previous state.

```
dbutility reload <data_source> <data_source>_control_tables.sav
```

Verifying the results

You can verify that the `dbscriptfixup` program successfully updated your control tables by executing a `redefine` command for the data source with the `-R` option. If the command finds no changes in the table layouts, then you know that you safely use the Client Configurator and that all the changes that you made via user scripts are preserved.

Start Enterprise Server

You can start DATABridge Enterprise Server using the shortcuts installed on the Windows Start menu or from a command prompt session. When you start Enterprise Server from the Start menu, Enterprise Server starts the application with Administrator privileges (required on Vista and Windows 2008). Administrator privileges are only required to control the DBDirector service on Windows XP, 2003, and 2000. Additionally, Enterprise Server can be started by DBDirector anytime DBDirector receives a connection request from a DATABridge Client.

From the Enterprise Server **Help** menu, you can find instructions for importing sources (upgrades), creating sources (new installations), and configuring the program.

To start from the Start menu

- From the **Start** menu, select **All Programs > Attachmate DATABridge 6.2 > DATABridge Enterprise > Configure Enterprise** to run Enterprise Server with elevated administrator privileges.

When Enterprise Server starts, the DATABridge Enterprise window appears.

To start from a command session

- Navigate to the directory where you installed Enterprise Server and type the following:

```
DBEnterprise.exe
```

For information about command-line options, see the *DATABridge Enterprise Server Help*.

Installation Results

This section includes lists of files that are installed with each product.

In this section

OBJECT/DATABRIDGE Directory	51
Files Installed with DATABridge Host	53
SYMBOL/DATABRIDGE Directory	53
WFL/DATABRIDGE Directory	55
DATA Directory	56
PATCH Directory	57
Files Installed with DATABridge Enterprise Server	59
Files Installed with the DATABridge Client and Client Console	60

OBJECT/DATABRIDGE Directory

The DATABridge Host files are copied to the usercode designated at installation.

Filename	Description
OBJECT/DATABRIDGE/AUDITMIRROR	Object code for the DATABridge AuditMirror Accessory
OBJECT/DATABRIDGE/BCNOTIFY	Object code for the BCNOTIFY utility
OBJECT/DATABRIDGE/SPAN	Object code for the DATABridge Span Accessory
OBJECT/DATABRIDGE/DBINFO	Object code for the DATABridge Database Info utility
OBJECT/DATABRIDGE/ENGINE	Object code for DATABridge Engine library
OBJECT/DATABRIDGE/LISTER	Object code for the DATABridge Lister Accessory
OBJECT/DATABRIDGE/SAMPLE/SQLGEN	Object code for the sample DATABridge SQLGen Accessory
OBJECT/DATABRIDGE/SAMPLE/DASDLGEN	Object code for the sample DATABridge DASDLGen Accessory

OBJECT/DATABRIDGE/SAMPLE/ COBOLGEN	Object code for the sample DATABridge COBOLGen Accessory
OBJECT/DATABRIDGE/SAMPLE/ AUDITCLOSE	Object code for the sample DATABridge Audit Close utility
OBJECT/DATABRIDGE/SAMPLE/READDOC	Object code for the sample DATABridge ReadDoc Accessory
OBJECT/DATABRIDGE/SAMPLE/MINISPAN	Object code for sample DATABridge MiniSpan Accessory
OBJECT/DATABRIDGE/SAMPLE/REFORMAT	Object code for sample data item conversion routines
OBJECT/DATABRIDGE/SAMPLE/MINILISTER	Object code for the sample DATABridge MiniLister Accessory
OBJECT/DATABRIDGE/SAMPLE/COBOLFORMAT	Object code for the sample COBOL format utility
OBJECT/DATABRIDGE/SAMPLE/EXTRACTADDRESS	Object code for the sample ExtractAddress library
OBJECT/DATABRIDGE/SAMPLE/ENCRYPT	Object code for the sample encryption library
OBJECT/DATABRIDGE/SERVER	Object code for the DATABridge Server Accessory
OBJECT/DATABRIDGE/TANKER	Object code for the DATABridge Tanker Accessory
OBJECT/DATABRIDGE/SUPPORT	Object code for the DATABridge Support Library
OBJECT/DATABRIDGE/SNAPSHOT	Object code for the DATABridge Snapshot Accessory
OBJECT/DATABRIDGE/GENFORMAT	Object code for the DATABridge GenFormat program
OBJECT/DATABRIDGE/AUDITTIMER	Object code for the DATABridge AuditTimer program
OBJECT/DATABRIDGE/AUDITSUPPORT	Object code for the DATABridge Plus library

OBJECT/DATABRIDGE/COBOLSUPPORT	Object code for DATABridge CobolSupport library
OBJECT/DATABRIDGE/KEYENTRY	Object code for product key library
OBJECT/DATABRIDGE/CHANGEUSER	Object code for the DATABridge ChangeUser library. ChangeUser changes the usercode of a Server Accessory Worker in cases where the SOURCE specifies a USERCODE, so the Worker will appear in response to a CANDE ?J (jobs) command or the ODT or MARC command A USER <usercode>, which lists all of the active programs running under usercode.

Files Installed with DATABridge Host

This section describes each of the files installed with DATABridge Host software.

DATABridge software is organized into the following directories:

Directory	Description
OBJECT/DATABRIDGE/=	Executable files
SYMBOL/DATABRIDGE/=	Source files
WFL/DATABRIDGE/=	WFL job files
DATA/=	Parameter and data files
PATCH/=	Source files

SYMBOL/DATABRIDGE Directory

The DATABridge Host files are copied to the usercode designated at installation.

Filename	Description
SYMBOL/DATABRIDGE/SAMPLE/LOAD	Source code for loading the sample DMSII database (COBOL file type)

SYMBOL/DATABRIDGE/SAMPLE/SQLGEN	Sample source code for generating an SQL script to create tables that correspond to a DMSII database. (ALGOL file type)
SYMBOL/DATABRIDGE/SAMPLE/COBOLGEN	Sample source code for generating COBOL file layouts corresponding to a DMSII database (ALGOL file type)
SYMBOL/DATABRIDGE/SAMPLE/AUDITCLOSE	Sample source code for closing a DMSII audit file (ALGOL file type)
SYMBOL/DATABRIDGE/ SAMPLE/READDOC	Sample source code for reading audit records (ALGOL file type)
SYMBOL/DATABRIDGE/SAMPLE/DASDLGEN	Sample source code for generating a DMSII DASDL source corresponding to a DMSII database (ALGOL file type)
SYMBOL/DATABRIDGE/SAMPLE/DATABASE	Source code for defining the sample DMSII database (DASDL file type)
SYMBOL/DATABRIDGE/SAMPLE/MINISPAN	Sample source code for writing a COBOL program similar to the Span Accessory (COBOL74 file type)
SYMBOL/DATABRIDGE/SAMPLE/REFORMAT	Sample source code for writing data item conversion routines in a REFORMAT library (ALGOL file type)
SYMBOL/DATABRIDGE/SAMPLE/MINILISTER	Sample source code for writing a COBOL program similar to the Lister Accessory (COBOL74 file type)
SYMBOL/DATABRIDGE/SAMPLE/COBOLFORMAT	Sample source code for writing a formatting routine in COBOL (COBOL74 file type)
SYMBOL/DATABRIDGE/SAMPLE/EXTRACTADDRESS	Sample source code for a library that will extract addresses and build VIRTUAL records (COBOL file type)
SYMBOL/DATABRIDGE/SUPPORT	Source code for the Support Library (ALGOL file type)
SYMBOL/DATABRIDGE/INTERFACE	Source code INCLUDE file for the API (ALGOL file type)
SYMBOL/DATABRIDGE/INTERFACE/FC	Source code for the COBOL API; contains File Control declarations (COBOL74 file type)

SYMBOL/DATABRIDGE/INTERFACE/FD	Source code for the COBOL API; contains File Description declarations (COBOL74 file type)
SYMBOL/DATABRIDGE/INTERFACE/PD	Source code for the COBOL API; contains Procedure Division statements (COBOL74 file type)
SYMBOL/DATABRIDGE/INTERFACE/WS	Source code for the COBOL API; contains Working Storage declarations (COBOL74 file type)
SYMBOL/DATABRIDGE/COBOLSUPPORT	Source code for providing entry points to COBOL Accessories for filtering and formatting routines in the Support Library (ALGOL file type)

WFL/DATABRIDGE Directory

The DATABridge Host files are copied to the usercode designated at installation.

Filename	Description
WFL/DATABRIDGE/AUDITMIRROR	Work flow that receives mirrored audit files on the secondary computer
WFL/DATABRIDGE/BCNOTIFY	Work flow for executing BCNOTIFY
WFL/DATABRIDGE/COMP	Work flow for compiling a DATABridge sample program or the Support Library
WFL/DATABRIDGE/SPAN	Work flow for executing DATABridge Span
WFL/DATABRIDGE/DBINFO	Work flow for executing the DATABridge Database Info utility
WFL/DATABRIDGE/LISTER	Work flow for executing the Lister accessory
WFL/DATABRIDGE/NOTIFY	Work flow for notifying DATABridge Server of additional audit information
WFL/DATABRIDGE/SAMPLE/SQLGEN	Work flow for executing the SQLGen sample Accessory
WFL/DATABRIDGE/SAMPLE/ READDOC	Work flow for executing the ReadDoc sample Accessory
WFL/DATABRIDGE/SAMPLE/ COBOLGEN	Work flow for executing the COBOLGen sample Accessory

WFL/DATABRIDGE/SAMPLE/DATABASE	Work flow for creating and populating the sample database (BANKDB) supplied with DATABridge
WFL/DATABRIDGE/SAMPLE/MINISPAN	Work flow for executing the MiniSpan sample Accessory
WFL/DATABRIDGE/SAMPLE/AUDITCLOSE	Work flow for executing the Audit Close sample Accessory
WFL/DATABRIDGE/SAMPLE/MINILISTER	Work flow for executing the MiniLister sample Accessory
WFL/DATABRIDGE/SAMPLE/REMOVEAUDIT	Work flow for removing audit files
WFL/DATABRIDGE/SERVER	Work flow for executing DATABridge Server
WFL/DATABRIDGE/TANKER	Work flow for executing the Tanker Accessory
WFL/DATABRIDGE/INCLUDE/DBTITLE	Work flow that parses the DMSII database title for all other WFLs
WFL/DATABRIDGE/INSTALL	Work flow for installing the DATABridge software
WFL/DATABRIDGE/SNAPSHOT	Work flow for executing the Snapshot Accessory
WFL/DATABRIDGE/COPYAUDIT	Work flow that can be used in place of the DMSII COPYAUDIT WFL to postpone removal of audit files
WFL/DATABRIDGE/AUDITTIMER	Work flow for executing the AuditTimer utility

DATA Directory

The DATABridge Host files are copied to the usercode designated at installation.

Filename	Description
DATA/AUDITMIRROR/SAMPLE/CONTROL	Sample parameter file for the DBAuditMirror Accessory (SEQDATA file type)
DATA/LOAD/SAMPLE/DATABASE	Data for the sample database that you can use with DATABridge
DATA/ENGINE/CONTROL	Parameter file that contains the key information for running this release of DATABridge, as well as other options for DBEngine operation

DATA/ENGINE/SAMPLE/CONTROL	Sample DBEngine parameter file for specifying database-specific DBEngine parameters (SEQDATA file type)
DATA/LISTER/SAMPLE/CONTROL	Sample parameter file for the Lister Accessory (SEQDATA file type)
DATA/SERVER/SAMPLE/CONTROL	Sample parameter file for DATABridge Server (SEQDATA file type)
DATA/GENFORMAT/SAMPLE/CONTROL	Sample parameter file for the GenFormat program (SEQDATA file type)
DATA/AUDITMIRROR/SAMPLE/CONTROL	Sample parameter file for the AuditMirror program (SEQDATA file type)
DATA/AUDITTIMER/SAMPLE/CONTROL	Sample parameter file for the AuditTimer program (SEQDATA file type)
DATA/DATABRIDGE/README	CANDE text file that lists important notices and last minute information about DATABridge
DATA/DATABRIDGE/API/README	CANDE text file that lists important notices about using the DATABridge Programmer's Reference
DATA/DMSIICLIENT/README	CANDE text file that lists important notices about DATABridge DMSII Client
DATA/TWIN/README	CANDE text file that lists important notices about DATABridge Twin
DATA/AUDITSUPPORT/README	CANDE text file that lists important notices about DATABridge Plus

PATCH Directory

The DATABridge Host files are copied to the usercode designated at installation.

Filename	Description
PATCH/DATABRIDGE/DASDL/TWIN	A DASDL patch you must include in your database to run DATABridge Twin if your restart data set does not have the required fields
PATCH/DATABRIDGE/SAMPLE/SUPPORT/STAR TUP	Sample startup procedure for a Support Library
PATCH/DATABRIDGE/SAMPLE/SUPPORT/VIRT UAL	Sample skeleton patch to the Support Library for a VIRTUAL TRANSFORM routine
PATCH/DATABRIDGE/SAMPLE/SUPPORT/REFO RMAT	Sample INTERNAL REFORMAT program

DATABridge 6.2

PATCH/DATABRIDGE/SAMPLE/SUPPORT/SHUTDOWN	Sample shutdown procedure for a Support Library
PATCH/DATABRIDGE/SAMPLE/SUPPORT/ERRORHANDLER	Sample error manager routine
PATCH/DATABRIDGE/SAMPLE/SUPPORT/FORMATADDRESS	Sample formatting routine for VIRTUAL data sets

Files Installed with DATABridge Enterprise Server

Use this document to verify the default installation results for DATABridge Enterprise Server.

In addition to installing the Enterprise Server files, the setup program adds shortcuts to the Start menu from which you can configure a source and view the configuration and log files folder.

The following files are installed to C:\Program Files\Attachmate\DATABridge\6.2\Enterprise:

Filename	Description
Help folder	The DATABridge Enterprise Server Help files (.html) which are viewable from the program by selecting the Help menu or by pressing the F1 key.
Support folder	Header files and DBEUser.lib for compiling user-written libraries
Support\MakeUserLib.cmd	Batch file for building user-written libraries
DBDirector.exe	Windows service that listens for requests from DATABridge Clients and then initiates the Enterprise Server application
DBEnterprise.exe	Enterprise Server executable file
DBUI.dll	The optional message and dialog text for Enterprise Server, which can be translated into other (non-English) languages
EnumDisk.exe	Enterprise Server utility that lists the MCP disks available on the server where Enterprise Server is installed
FinishMirrored.cmd	Sample batch file to run whenever an audit file is successfully mirrored to the secondary system.
LINCLOG.dll	LINC log FileXtract Reader library
Notify.cmd	Sample batch file to run when the DATABridge Server accessory signals the availability of more audit files to process

Files Installed with the DATABridge Client and Client Console

During installation, the DATABridge Client 6.2 copies files to the install directory and a client-specific directory (such as SQLServer). On Windows, the install directory is located at C:\Program Files\Attachmate\DATABridge\6.2. In addition, the Attachmate Installer Program installs files that repair, reinstall, and remove the program to a Setup folder in this location.

In the following tables, the filenames represent both UNIX and Windows files. Windows extensions are provided in brackets ([]). The following files are copied to the install directory:

Filename	Description
bconsole[.exe]	The Batch Console automates routine Client tasks by allowing command files/shell scripts launched by the Client service to interact with the service. For more information, see the <i>DATABridge Client Administrator's Guide</i> .
DATABridge_Messages.dat	A binary file that the DATABridge service/daemon uses to retrieve the text associated with error status codes generated by various DATABridge components.
DBCIntControl[.exe]	The service (Windows) or daemon (UNIX) that automates most Client operations. It handles operator requests from the Client Console and routes all log and informational messages. The service has no effect on dbutility command-line operations.
dbctrlconfigure[.exe]	A command-line program that implements the import and export commands for the service configuration file. It converts the service configuration file (dbcontrol.cfg) from its native binary format to text format (.ini) and back using the export and import commands.
logmaint[.exe]	A utility that allows you to delete all log files from the service and the individual data source directories except for the most recent N. Run this utility from the working directory for the service or the data source whose log files you want to manage. The number of files to retain are specified on the command line for logmaint as optional parameters. When used for the client, it has two parameters. The first parameter is for the DBClient and dbutility log files. The second parameter is for DBCInCfgServer log files. The parameters default to 10 and can be set to a value as low as 2.
readme.txt	A text file that contains late-breaking information for the product.

setfilesecurity.exe (Windows only) A Windows program that lets you set file security for all files and directories in the Working Directory, (which includes changes to the Windows registry). This program functions the same as the utility started by the installer, except that it doesn't allow you change the system or user path. It must be run from an account that has Administrator privileges.

The following files are copied to the client-specific directory:

Filename	Description
bcp_auditor.exe (Windows only)	A program that scans the bcp output to determine if the bcp utility was successful. The bcp_auditor utility sets the exit code correctly. This utility applies only to Microsoft SQL Server databases.
DBClient[.exe]	A Client program that is launched by the service. DBClient handles the processing of DMSII data and updates the same as dbutility, except that it runs as a background run and uses the Client Console to display its output and interact with the operator.
DBCIntCfgServer[.exe]	A program that handles all requests from the Client Console specific to a data source. These requests include updating the client configuration file, providing access to the client control tables, and handling the Client Configurator. Like DBClient, this program is run by the service as a background run.
*dbeatran.dll *dbgaiji.smp *dbtrans_jbis8.smp *dbtrans_v24jbis8.smp	Japanese double-byte translation DLL and sample configuration files. Depending on which character set the mainframe uses, copy the appropriate dbtrans file to the config directory as dbtrans.cfg. Also, copy the file dbgaiji.smp to the config directory as dbgaiji.cfg.
dbfixup[.exe]	A program used for updating existing client control tables when upgrading from a previous client release.
dbpwenc[.exe]	A program for encoding the relational database and DBServer (or DBEnterprise Server) passwords for text based configuration files.

Note: Passwords set in the Client Console are automatically encoded in binary configuration files.

dbscriptixup[.exe]	An program that modifies the Client control tables according to changes specified by the user scripts and enables the Client Configurator to make future modifications to the table layout.
dbutility[.exe]	A program that runs the DATABridge Client from a command line.
getlogtail.exe (Windows only)	A program that extracts the tail of the current log file and writes it to the file <code>trace.log</code> .
migrate[.exe]	The upgrade program that updates configuration settings and creates the working directory structure. It copies the updated configuration files and any user scripts to the new working directory structure.
splitter[.exe]	A utility that splits large trace files into smaller files. Used primarily for sending files to Attachmate for troubleshooting.
dumpnullrecs[.exe]	A program that displays the content of the NULL record file for a given data source.

*Installed only when the Japanese language feature is selected.

Client Console Files

Files for the Client Console are installed in the following two directories at C:\Program Files\Attachmate\DATABridge\6.2.

Directory	Description
DBConfig	Contains the configuration file, initialization file, and plugins subdirectory. The plugins subdirectory which contains required Eclipse plugins and source code plugins for the DATABridge Client Configurator.
DBConsole	Contains the configuration file, initialization file, and plugins subdirectory. The plugins subdirectory which contains required Eclipse plugins and source code plugins for the DATABridge Client Console. The JRE subdirectory contains files for the Java Runtime Environment.